



# ANTIRUST TERAMI LN-H

## Barium-free long-term lubricating-oil-type high-viscosity rust preventive oil

ANTIRUST TERAMI LN-H is a rust preventive oil for the processing parts and the machine parts, which passes NP-9 in JIS standard. ANTIRUST TERAMI LN-H, which does not contain petrolatum, provides good working efficiency, good removal of oil film and high protection performance against corrosion.

### ● SPECIAL FEATURES

#### 1. Excellent Rust Prevention

ANTIRUST TERAMI LN-H delivers excellent protection from rust due to the most suitable mineral oil and additives.

#### 2. Low Risk of Fire

ANTIRUST TERAMI LN-H has high flash point exceeds 150°C and can be used with low risk of fire.

#### 3. Good Removal

Film of ANTIRUST TERAMI LN-H is easily removed with a petroleum solvent or alkaline process cleaner.

### ● APPLICATIONS

For various processing parts and machine parts

### ● COATING METHOD

Immersion, Spraying, Brushing

### ● CONTAINERS

200-liter drums and 20-liter cans

### ● Typical Properties of ANTIRUST TERAMI LN-H

Appearance		Brown Liquid
Color	(ASTM)	L5.5
Density	(15°C) g/cm <sup>3</sup>	0.875
Flash point	(COC) °C	154
Viscosity	(40°C) mm <sup>2</sup> /s	28.5
Water displacement	(JIS K2246)	No rust
Metal strip corrosion	(JIS K2246 NP-3)	Passed
Humidity cabinet test	(Class A holding time) h	>1200
Salt spray test	(Class A holding time) h	> 48
Protection	(Indoors) months	6
Type of film		Non-dry and transparent film
Film thickness	μm	7.0

Note: The typical properties may be changed without notice. (April 2009).



## Handling Precautions

▼ Follow these precautions when handling this product.

<b>! CAUTION</b>  <b>Handling Precautions</b>	<ul style="list-style-type: none"><li>● <u>Inflammation can occur if oil enters the eyes.</u> When handling this oil, wear <u>protective goggles</u> or take other measures to <u>prevent eye contact</u>.</li><li>● <u>Inflammation can occur if oil comes into contact with skin.</u> When handling this oil, wear <u>protective gloves</u> or take other measures to <u>prevent skin contact</u>.</li><li>● Do not eat. (Ingestion can cause diarrhea and nausea.)</li><li>● It is possible to cut your hands when opening the container. Wear <u>protective gloves</u>.</li><li>● <u>Keep out of reach of children.</u></li><li>● Read the Material Safety Data Sheet (MSDS) for this product before using the product. Obtain the Material Safety Data Sheet from where you purchased the product.</li></ul>
<b>First Aid</b>	<ul style="list-style-type: none"><li>● In case of eye contact, rinse eyes thoroughly with clean water and consult with a physician.</li><li>● In case of skin contact, wash skin thoroughly with soap and water.</li><li>● If swallowed, do not induce vomiting. Consult with a physician immediately.</li></ul>
<b>Disposal of Used Oil and Containers</b>	<ul style="list-style-type: none"><li>● Do not apply pressure to empty containers. The containers may burst if pressure is applied.</li><li>● Do not weld, heat, drill, or cut the containers. The remaining oil may ignite and the containers may explode.</li><li>● Follow all applicable laws and regulations when disposing of used oil or containers. If you are unsure of the proper disposal methods, consult first with the seller of the oil.</li></ul>
<b>Storage Method</b>	Seal the container tightly after use in order to prevent dirt, moisture, etc., from entering the oil. Store in a dark location. Avoid direct sunlight.